



Trailer Model: GTFF202-40

Weight: _____ ± lbs

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance
40'	8' 6"	48"	59"	57"	10 ½"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44" Standard
Side Rails	6" Channel
Crossmembers	4" Jr. I-Beams
Spacing	12"
Stake Pockets	24" center, both sides, front & rear, with rubrails
Head Rack, Tool Box	
Web Winches 12 with straps driver side	
Decking/Flooring	
Main Decking	1 ¾" Apitong Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Wide Turn Indicators	
Tires & Rims	
Tires	11R x 22.5 "H"
Rims	8.25 x 22.5 10 Hole Hub Piloted Steel
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	30"
Swing Clearance	128"
5th Wheel Height	48"
King Pin	2" Heavy Duty

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 ½" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30
Spring Sliding Suspension	
2-Speed Landing Gear	
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

Dealer: