



Trailer Model: GTFF402-48

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
48'	8' 6"	48" (Unloaded)	59" (Nominal)	54" (Nominal)	68"	10"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	2
Centers	40" Standard	Axle Spacing	49"
Side Rails	6" Structural Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I-Beams on 8" Center	Brakes	16 1/2" x 7" - 25K
Stake Pockets	24" Center, both sides, front & rear, with rubrails	ABS	2S1M
Decking/Flooring		Axle 1	Fixed Type 30/30 NON ABS
Main Decking	1 3/8" Apitong Flooring	Axle 2	Fixed Type 30/30 ABS
Electrical		Tandem Air Ride Suspension	
Lights	LED Plus 2 - Rear Strobes	2-Speed Landing Gear	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R x 22.5 "H"	King Pin Setting	36"
Rims	8.25 x 22.5 Hub Piloted Steel	Swing Clearance	68"
Finish		5th Wheel Height	48" (Unloaded)
Sandblast & Powder Coat		King Pin	2"
Mud Flaps & Reflective Tape		Dealer: 	
Options			
Wide Turn Indicators			
Head Rack, Removable			
Twist locks: 2 for 20' Container, or 1 for 40' container.			
Sliding Winch track road side, and straps both sides.			
Corrugated aluminum side racks, lock in place with J-Locks.			