



Trailer Model: GTFF402-40

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
40'	8' 6"	49" (Unloaded)	59"	55"	74"	10"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	2
Centers	42"	Axle Spacing	49"
Side Rails	6" @ 6.5# Structural Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I-Beam on 12" Center	Brakes	16 1/2" x 7" - 25K
Stake Pockets	24" Center, both sides, front & rear, with rubrails	ABS	2S1M
Decking/Flooring		Axle 1	Fixed Type 30/30 NON ABS
Main Decking	1 3/8" Apitong Flooring	Axle 2	Fixed Type 30/30 ABS
Electrical		Tandem air ride sliding suspension, with manual dump valve	
Lights	LED Plus 2 - Rear Strobes	2-Speed Landing Gear.	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R x 22.5 "H"	King Pin Setting	30"
Rims	8.25 x 22.5 Hub Piloted Steel	Swing Clearance	74"
Finish		5th Wheel Height	49"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		Dealer:	
Options			
Wide Turn Indicators			
Head Rack, Removable			
Sliding Winch track road side, with straps.			
Steel underbody mount Tool Box			
Twist Locks : 1 for 20'			