



**Trailer Model: GTFF402-48**

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
48'	8' 6"	49" (Unloaded)	59"	58"	74"	16"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44"
Side Rails	6" @ 6.5# Structural Steel Channel
Crossmembers	4" Jr. I-Beams on 12" Centers.
Stake Pockets	24" center, both sides, front & rear, with rubrails
Decking/Flooring	
Main Decking	1 3/8" Apitong Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	295/75R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options   Additions	
Wide Turn Indicators	
Head Rack, Removable	
Steel storage box underside of trailer.	
Sliding Winch track road side, and straps both sides.	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 NON ABS
Axle 2	Fixed Type 30/30 ABS
Spring ride sliding suspension	
2-Speed Landing Gear.	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	30"
Swing Clearance	74"
5th Wheel Height	49" (unloaded)
King Pin	2" Heavy duty

**Dealer:**