



Trailer Model: GTFF503-32

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
32'	8' 6"	49"	58"	58"	84"	12 1/2"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	3
Centers	44 1/4"	Axle Spacing	54 1/2"
Side Rails	Structural Steel Channel	Axle Capacity	25,000lbs
Crossmembers	Jr. I-Beams on 12" Centers	Brakes	16 1/2" X 7" - 25K
D Rings	10 each side	ABS	4S2M
Web Winches and rubrails.		Axle 1	Fixed Type 30/30 ABS
Decking/Flooring		Axle 2	Fixed Type 30/30 ABS
Main Decking	Steel Smooth Plate, 1/4" Thick Covering The Entire Deck Surface. Allows 4 Tank Locator Brackets Installation	Axle 3	Fixed Type 30/30 ABS
Electrical		Tri-axle spring ride suspension	
Lights	LED Plus 2 - Rear Strobes	Heavy Duty Mark V Series Landing Gear With Sand Shoe And Wheel 10" X 16"	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R x 22.5 "H"	King Pin Setting	20"
Rims	8.25 x 22.5 Hub Piloted Steel	Swing Clearance	84"
Finish		5th Wheel Height	49"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		Dealer:	
Options			
Placard holders & Placard with 8 Panels			
Web Winches			
Toolbox on road side, in the below main deck center.			
4 Swivel hoist rings			