



Trailer Model: GTFV503-53-32

Weight: Apx. _____ ± lbs

| Overall Length | Overall Width | Gooseneck Length | Deck Height | Load Well Length | Beavertail | Ground Clearance |
|----------------|---------------|------------------|-------------|------------------|------------|------------------|
| 53' | 8' 6" | 10' | 37" | 31' 11" | 40" | 12" |

| Main Deck | |
|-----------------------------|---------------------------------------|
| Main Beam | 100 KSI flanges and webs. |
| Centers | 40" Standard |
| Side Rails | Structural Steel Channel |
| Crossmembers | 10" & 4" on 12" Centers |
| Outriggers | Standard Outriggers |
| D-Rings | 12 each side |
| Decking/Flooring | |
| Main Decking | 2" Apitong Flooring |
| Electrical | |
| Lights | LED Plus 2 - Rear Strobes |
| Connector | 7 Way SAE Connector |
| Tires & Rims | |
| Tires | 235/75R X 17.5 "H" |
| Rims | 6.75 x 17.5, 8 hole-hub piloted steel |
| Rear Deck Options | |
| Beavertail 40" | |
| Rear Ramps 108" x 36" | |
| Hydraulic, BI - FOLD | |
| Finish | |
| Sandblast & Powder Coat | |
| Mud Flaps & Reflective Tape | |
| Flag Holders | |

| Axles, Suspension, & Running Gear | |
|-----------------------------------|--|
| # of Axles | 3 |
| Axle Spacing | 50" |
| Axle Capacity | 25,000lbs |
| Brakes | 12.25" x 7.5" Full Air Brakes with Spring Parking Brakes |
| ABS | 4S3M |
| Axle 1 | Fixed Type 30/30 |
| Axle 2 | Fixed Type 30/30 ABS |
| Axle 3 | Fixed Type 30/30 ABS |
| Air Ride Suspension. | |
| 17" Travel, 2-Speed Landing Gear. | |
| Gooseneck | |
| King Pin Style | Fixed |
| King Pin Setting | 18" |
| Swing Clearance | 98" |
| 5th Wheel Height | 49" |
| King Pin | 2" Heavy Duty |
| 48" head board w/ center opening | |
| Dealer: | |