



Trailer Model: GTFS402-45-34

Weight: _____ ± lbs

Overall Length	Overall Width	Gooseneck Length	Deck Height	Load Well Length	Ground Clearance
45'	8' 6"	10' 10"	43" LOADED	34' 2"	10"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	42" Standard
Side Rails	Structural Steel Channel
Crossmembers	4 on 12" Centers.
Neck	Full Width
Web Winches	10 each Side
D-Rings	6 each side
Stake Pockets	24" center, both sides, front & rear, with rubrails.
Decking/Flooring	
Main Decking	1 3/8" Oak Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 10 Hole Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30
Axle 2	Fixed Type 30/30 ABS
Spring Ride Suspension.	
17" Travel, 2-Speed Landing Gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	16"
Swing Clearance	92 1/2"
5th Wheel Height	49 5/8"
King Pin	2" Heavy Duty

Dealer: