



**Trailer Model: GTFV403-50-30**

**Weight: Apx. \_\_\_\_\_ ± lbs**

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Ground Clearance
50' 5"	8' 6"	12' 4"	21' 10"	36"	12"

Main Deck	
Main Beam	T-1 Steel 16" Fabricated I-Beam
Centers	41"
Side Rails	12" Channels
Crossmembers	10" & 4"
Spacing	12"
#Of D-Rings	9 Ea. Side
Concentrated Load	100,000 lbs in 12'
Decking/Flooring	
Main Decking	2" Nominal Apitong
Wheel Covers	Steel Covered D-Plate w/grouser bars
Rear Deck Options	
Bevertail 40" Steel w/grouser bars	
Rear Ramps 136" X 36" Bi-Fold	
Hydraulic Ramp System	
Steel Cleated	
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30 Non-ABS
Spring Ride Suspension	
2-Speed Landing Gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	18"
Swing Clearance	76"
5th Wheel Height	48"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
<b>Dealer:</b>	