



**Trailer Model: GTFF121-30**

**Weight: Apx. \_\_\_\_\_ ± lbs**

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance
30'	8'	48"	59"	54"	10 1/4"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	36" Standard
Side Rails	6" Structural Channel
Crossmembers	4" Jr. I Beams on 8" Centers
Stake Pockets	24" center, both sides, front & rear, with rubrails, rear with double pipe spools
Decking/Flooring	
Main Decking	1 3/8" Apitong Shiplap Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	11R X 22.5 "H"
Rims	8.5 x 22.5 Hub Piloted Steel
Options	
Steel removable header rack 42" in height	
Spare tire wheel assembly with basket carrier under chassis curside	
Removable stake bodies all sides	
Rubber bumpers on rear	

Axles, Suspension, & Running Gear	
# of Axles	1
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Spring ride suspension	
2-Speed Landing Gear	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	36"
Swing Clearance	98 1/2"
5th Wheel Height	48"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

**Dealer:**