



Trailer Model: GTFF202-48

Weight: Apx. _____ ± lbs

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance
48' 4"	8' 6"	49" (Unloaded)	60 1/2"	58 1/2"	12"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44" Standard
Side Rails	6" Channel
Crossmembers	4" Jr. I-Beams
Stake Pockets	24" center, both sides, front & rear, with rubrails.
Spacing	12"
Decking/Flooring	
Main Decking	1 3/8" Apatong Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	11R x 22.5 "H"
Rims	8.25 x 22.5 Hole Hub Piloted Steel
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	30"
5th Wheel Height	49"
King Pin	2" Heavy Duty
Swing Clearance	128"

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30
Spring Sliding Suspension	
2-Speed Landing Gear	
Options	
Wide Turn Indicators	
Head Rack Fixed, Hubometer, Tool Box	
Web Winches 12 with straps driver side	
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

Dealer: