



Trailer Model: GTFV403-53-37

Weight: _____ lbs

Overall Length	Overall Width	Gooseneck Length	Deck Length	Deck Height	Ground Clearance
53'	8' 6"	16'	37' 4"	38"	11 3/4"

Main Deck	
Main Beam	16" Fabricated I-Beam
Centers	40"
Side Rails	12" Channel
Crossmembers	10" & 4"
Spacing	12"
D-Rings	9 Each Side
Sliding Winch Track with 10 winches & straps	
Concentrated Load	80,000 lbs in 12'
Decking/Flooring	
Main Decking	2" Apitong
Wheel Covers	Steel Covered S-Plate
2 - Tool Boxes one each side, mounted under deck	
Electrical	
Lights	LED Plus -2 Rear Strobe
Connector	7 Way SAE Connector
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Rear Deck Options	
Removable Aluminum Rear Ramps 108" x 20" Stored on side of trailer	

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	49"
Axle Capacity	25,000 lbs
Brakes	16 1/2" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Super lift Type 30 Non-ABS
Air Ride Suspension	
2-Speed Landing Gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	18"
Swing Clearance	86"
5th Wheel Height	48"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Dealer:	