



Trailer Model: GTFF402-40

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance
40'	8' 6"	52" (Loaded)	63"	59"	11"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44" Standard
Side Rails	6" Channel
Crossmembers	4" Jr. I-Beams
Spacing	12"
Stake Pockets	Both sides 24" center, 5 front & rear with rubrails.
Decking/Flooring	
Main Decking	1 3/8" Apitong
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	11R x 22.5 "H"
Rims	8.25 x 22.5 Hole Hub Piloted Steel
Options	
Wide Turn Indicators	
Head Rack, Hubometer, Tool Box	
Web Winches Fixed 10 with straps driver side	
Twist Locks each side for 20' container, rear impact guard, rear bumper	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Air Ride Sliding Suspension	
2-Speed Landing Gear	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	30"
Swing Clearance	128"
5th Wheel Height	52"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

Dealer: