



**Trailer Model: GTFF402-48**

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance
48'	8' 6"	52" (Unloaded)	63" (Nominal)	59" (Nominal)	10 1/2"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	2
Centers	44" Standard	Axle Spacing	49"
Side Rails	6" Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I-Beams	Brakes	16 1/2" x 7" - 25K
Spacing	12"	ABS	2S1M
Stake Pockets	24" center, both sides, 5 front & rear, with rubrails.	Axle 1	Fixed Type 30/30 ABS
<b>Decking/Flooring</b>		Axle 2	Fixed Type 30/30
Main Decking	1 3/8" Apitong 2 Fasteners per Board	Air Ride Sliding Suspension (28' Tuck Axle)	
<b>Electrical</b>		2-Speed Landing Gear	
Lights	LED Plus 2 - Rear Strobes	<b>King Pin and Swing Clearance</b>	
Connector	7 Way SAE Connector	King Pin Style	Fixed
<b>Tires &amp; Rims</b>		King Pin Setting	30"
Tires	11R x 22.5 "H"	Swing Clearance	128"
Rims	8.25 x 22.5 10 Hole Hub Piloted Steel	5th Wheel Height	52"
<b>Options</b>		King Pin	2" Heavy Duty
Wide Turn Indicators		<b>Finish</b>	
Head Rack, Hubometer, Tool Box		Sandblast & Powder Coat	
Web Winches 12 with straps driver side		Mud Flaps & Reflective Tape	
2 Twist Locks each Side for 20' Container, Rear Impact Guard, Rear Bumper		<b>Dealer:</b>	