



Trailer Model: GTFF402-48

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
48'	8'6"	48" loaded	59"	54"	104"	14"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	2
Centers	44" Standard	Axle Spacing	49"
Side Rails	6" Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I-Beams	Brakes	16 1/2" x 7" - 25K
Stake Pockets	24" center, both sides, front & rear, with rubrails	ABS	2S1M
Decking/Flooring		Axle 1	Fixed Type 30/30 ABS
Main Decking	1 3/8" Apitong	Axle 2	Fixed Type 30/30
Electrical		Tandem spring ride suspension.	
Lights	LED Plus 2 - Rear Strobes	2-Speed Landing Gear.	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R/75R x 22.5 "H"	King Pin Setting	30"
Rims	8.25 x 22.5 Hole Hub Piloted Steel	Swing Clearance	125"
Finish		5th Wheel Height	49"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		Dealer:	
Options			
Wide Turn Indicators			
12 Web Winches with Straps			
Toolbox, Hubometer 10D Rings each side			
Aluminium Stakes every 4"			