



Trailer Model: GTFH503-50-30

Weight: Apx. _____ ± lbs

| Overall Length | Overall Width | Gooseneck Length | Load well Length | Load well Height | Swing Clearance | 5th Wheel Height | Hydraulic Tail |
|----------------|---------------|------------------|------------------|------------------|-----------------|------------------|----------------|
| 50' | 8' 6" | 10' | 32' | 36" (Loaded) | 85" | 48" | 8' |

| Main Deck | |
|-----------------------------|------------------------------------|
| Main Beam | Fabricated I-Beam. |
| Crossmembers | Jr. I-Beams on 12" Centers |
| # Of D-Rings | 10 per side |
| Stake Pockets | Front & Sides |
| Decking/Flooring | |
| Main Decking | 1.375" Apatong flooring |
| Electrical | |
| Lights | LED Plus 2 - Rear Strobes |
| Connector | 7 Way SAE Connector |
| Tires & Rims | |
| Tires | 235/70R X 17.5 "H" |
| Rims | 6.75 X 17.5 Hub piloted steel disc |
| Hydraulics | |
| Wet-line system | |
| 27 HP Kohler gas | |
| Finish | |
| Sandblast & Powder Coat | |
| Mud Flaps & Reflective Tape | |
| Flag Holders | |

| Axles, Suspension, & Running Gear | |
|---|----------------------|
| # of Axles | 3 |
| Axle Spacing | 49" |
| Axle Capacity | 25,000lbs |
| Brakes | 12 ¼ X 7 ½ |
| ABS | 2S1M |
| Axle 1 | Fixed Type 30/30 |
| Axle 2 | Fixed Type 30/30 |
| Axle 3 | Fixed Type 30/30 ABS |
| Air ride suspension, Dump Valve, 2-Speed landing gear | |
| Gooseneck | |
| King Pin Style | Fixed |
| King Pin Setting | 16" |
| Swing Clearance | 86" |
| 5th Wheel Height | 48" |
| King Pin | 2" heavy duty |
| 20,000# Winch with 100' cable | |

Dealer: