



Trailer Model: GTBN553-58-30-HGG

Weight Apx. \_\_\_\_\_ ± lbs

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Rear Deck Length	Rear Deck Height	Ground Clearance
57' 5"	8' 6"	12' 11"	30'	22" loaded	14' 6"	42 3/8"	6"

Main Deck	
Main Beam	16" T-1 Steel Std.
Centers	41" Std.
Side Rails	16" T-1 Steel
Crossmembers	10"
Spacing	12"
Outriggers	Full Height Removable
# Of D-Rings	14 Each Side
Concentrated Load	110,000 lbs in 12'
Front Ramps	18" x 31" Std.
Rear Deck	
Riser	35° Rear Bridge Ramp
Rear Well Style	Boom & Bucket Well
# of D-Rings	2 Each Side
Set up for hydraulic powered flip	
Decking/Flooring	
Main Decking	1.75" Apitong Open Center
Wheel Covers	Steel Covered D-Plate
Well Decking	Removable V-Plate - Full Length
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Safety Night Light Package w/ Battery	
Tires & Rims	
Tires	275/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Outer Aluminum

Axles, Suspension & Running Gear	
# of Axles	4
Axle Spacing	54"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Super Lift Type 30 Non-ABS
Axle 4	Hydraulic Flip Type 30 Non-ABS
Air Ride Suspension - 25K, Auto Dump, Manual turn dial	
Hydraulics	
Wet Line Kit - Wing Nut Connection	
13HP - Gas Engine	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	16"
Swing Clearance	110"
5th Wheel Height	50"
King Pin	2"
Ride Height	5-Position
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

Dealer: