DLA Contract
SPE8EC-19-D-0039

GSA Contract
GS-30F-0027R

LOWBOY, 35 TON
35LB335379

PRD-00335379 A.1

LOWBOY, 35 TON
2 AXLE, DETACHABLE NON GROUND BEARING,
MAXIMUM PAYLOAD 70,000 LBS

Powdercoated by GLOBE TRAILERS

FEATURES & BENEFITS

HIGH QUALITY STEEL

Constructed with T-1 100K PSI yield strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

ADDED SECURITY



Globe Trailers air lock with safety bar and spring extended pin ensures that the gooseneck locking pin will remain secured even if air pressure is lost.

AIR BAGS

30K pound rated large diameter air bags are standard. This allows for lower operating pressure and higher capacity when needed.

WARRANTY

Globe Trailer's 10 year structural warranty on all lowboys is the best in the industry. Most competitors offer only a 5 year warranty. This shows how committed Globe Trailers is to it's customers.

STEMCO WHEEL WARRANTY

5 year wheel end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

COLOR CODED HOSES

Color coded air hoses allow for easy trouble shooting and maintenance.

LIGHTING SYSTEM

All Lighting is LED and mounted in rubber grommets to DOT standards.

22" DECK HEIGHT

With a standard deck height of 22", Globe Trailers have lower overall height, which allows taller loads to be hauled.

MULTI POSITION RIDE HEIGHT

Multi Position Ride Height options. Makes adjustments for various 5th wheel heights easy and allows for larger ground clearance or lower deck height.

BEAVERTAIL AT REAR

1'0" horizontal beavertail at rear of second axle.

COLOR OPTIONS

Globe Trailers can powder coat to the color of your choice.

FEATURES & BENEFITS

12" CROSS MEMBER SPACING



Standard 12" stubbed cross member spacing produces added strength to the trailer and also less stress on the decking, leading to a longer life of the decking material.

CENTRALLY LOCATED FITTINGS



Air, electric and hydraulic (when applicable) fittings are all centrally located at the base of the gooseneck inside a bolster. This makes for quick and easy connect and disconnect. The fittings are protected from possible contact with equipment being loaded or unloaded.

V-STYLE GUIDE

V-Style guide with front tapered beams helps position the gooseneck locking pin, which makes hooking up to a Globe Trailer fast and easy. The locking pin guide rim helps prevent the gooseneck locking pin from coming loose in transit.

DECKING OPTIONS

Oak: Standard.
Apitong: Best strength to weight ratios of natural woods.
Rumber: Composite which is impervious to fluids, mud, oil and UV rays.

MOUNTED SPARE TIRE

Optional spare tire that mounts securely on top of Gooseneck.

ALUMINUM COVER PLATE

Aluminum Cover Plate over Gooseneck

STANDARD OUTRIGGERS

Standard removable outriggers.

POLYURETHANE VS RUBBER BUSHING

Reduced Maintenance	Increased Maintenance
Increased Trailer Lifetime	Needs Replacement
Increased Trailer Performance	Reduces Trailer Performance
Weather Resistant	Damaged from Weather

Powdercoated by GLOBE TRAILERS

All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.

LOWBOY, 35 TON

35LB335379



Trailer Model: GTBN352-49-25-GG

Weight: Apx. 19,000 ± lbs

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Rear Deck Length	Rear Deck Height	Ground Clearance
49’ 4”	8’ 6”	11’ 2”	24’ 6”	22” loaded	13’ 8”	41”	6”

Main Deck	
Main Beam	16” T-1 Steel
Centers	40” Standard
Side Rails	16” T-1 Steel
Crossmembers	10” & 4”
Spacing	12”
Outriggers	Removable Standard
# Of D-Rings	11 each side
Front Ramps	Wood Filled, 22” x 50”
Concentrated Load	70,000 lbs in 12’
Rear Deck	
Riser	3:1 Ratio Wood Filled Full Width
Rear Well Style	Wood Filled Centerted 1/4” raised
# of D-Rings	4 each side
5” High Roller Stop Full-Width	
Decking/Flooring	
Main Decking	1.75” Apitong Full Width
Wheel Covers	Steel Covered D-Plate
Well Decking	Apitong
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Safety Night Light Package w/ Battery	
Tires & Rims	
Tires	255/70R x 22.5 “H”
Rims	8.25 x 22.5 Hub Piloted Steel
Hydraulics	
Wet Line Kit - Wing Nut Connection	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	54”
Axle Capacity	25,000lbs
Brakes	16 ½” x 7” - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 Non-ABS
Air Ride Suspension - 25K	
Manual Dump, Air Ride Adj.	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	16”
Swing Clearance	86”
5th Wheel Height	48”
King Pin	2”
Ride Height	5-Position
Aluminum Cover Plate on Gooseneck	
Chain Binder Rack (at rear of gooseneck)	
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Dealer:

Globe Trailers | 3101 59th Ave Drive East, Bradenton, Florida 34203

1-800-800-3484 | www.globetrailers.com | sales@globetrailers.com