



DROP DECK, 20 TON
20DP369300



PRD: 00369300 A.1



DROP DECK, 20 TON
2 AXLE, MAXIMUM PAYLOAD 40,000 LBS



HIGH QUALITY STEEL

NuStrength™
HIGH PERFORMANCE STEEL

NuStrength™ HR100

**HIGH
PERFORMANCE
STEEL**

ULTRA HIGH STRENGTH SHEET
100 KSI / 700 MPA SHEET STEEL COMPARISON

Melted and Manufactured in the USA

Constructed with T-1 100K PSI yield strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

HEAD RACK



Optional detachable steel bulkhead, 48" high with optional work lights.

WHEEL OPTIONS



All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.

SUSPENSION



Heavy Duty tandem suspension.

COLOR OPTIONS



Globe Trailers can powder coat to the color of your choice

LIFT RINGS



Four (4) lift rings on top of deck for lifting aboard ships.

LANDING GEAR



2 speed Landing Gear, allows for 160,000 lbs static load.

CONVEYER ROLLERS



3 rows of Conveyor rollers for USAF 463L pallets loaded with 10,000lbs of cargo.

LIGHTING SYSTEM



All Lighting is LED and mounted in rubber grommets to DOT standards.

D-RINGS



D'rings located on the side of the trailer.

STAKE POCKETS



Stake pockets located along the deck.

TIE DOWNS



Four (4) tie downs located on underside of trailer for air transportability. In accordance with -IAW MIL-HDBK-1791.

STEMCO WHEEL WARRANTY



5 year wheel end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

COLOR CODED HOSES



Color coded air hoses allow for easy trouble shooting and maintenance.

DECKING OPTIONS



Oak: Standard.
Apitong: Best strength to weight ratios of natural woods.
Rumber: Composite which is impervious to fluids, mud, oil and UV rays.

REAR BUMPER



DOT certified rear under ride bumper with high visibility reflective tape and rubber docking bumpers.

SPARE TIRE



Spare tire and holder located on underside of trailer deck.


POLYURETHANE VS RUBBER BUSHING



| | |
|-------------------------------|-----------------------------|
| Reduced Maintenance | Increased Maintenance |
| Increased Trailer Lifetime | Needs Replacement |
| Increased Trailer Performance | Reduces Trailer Performance |
| Weather Resistant | Damaged from Weather |



All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.



Trailer Model: GTFF202-40

Weight: Apx. : 14800 ± lbs

| Overall Length | Overall Width | Gooseneck Length | Swing Clearance | 5th Wheel Height | Load Well Length | Load Well Height | Ground Clearance |
|----------------|---------------|------------------|-----------------|------------------|------------------|------------------|------------------|
| 52' 6" | 8' | 10' | 84" | 48" | 42' | 40" (Loaded) | 10 7/8" |

| Main Deck | |
|--|---------------------------------------|
| Main Beam | 100 KSI flanges and webs. |
| Centers | 36" Standard |
| Side Rails | Structural Steel Channel |
| Crossmembers | 4" on 12" centers |
| D-Rings | 9 Per Side |
| Stake Pockets | 8 Per Side |
| Neck | Full Width, Steel Covered |
| 3 rows of Conveyor rollers for USAF 463L pallets loaded with 10,000lbs of cargo. | |
| Decking/Flooring | |
| Main Decking | 2", Oak Standard |
| Electrical | |
| Lights | LED Plus 2 - Rear Strokes |
| Connector | 7 Way SAE Connector |
| Tires & Rims | |
| Tires | 255/70R x 22.5 "H" |
| Rims | 8.25 x 22.5 10 Hole Hub Piloted Steel |
| Additional | |
| One (1) Spare Tire with Carrier, removable, mounted under deck. | |
| Steel Bulk Head 48"x96". | |

| Axles, Suspension, & Running Gear | |
|-----------------------------------|--------------------------|
| # of Axles | 2 |
| Axle Spacing | 49" |
| Axle Capacity | 25,000lbs |
| Brakes | 16 1/2" x 7" - 25K |
| ABS | 2S1M |
| Axle 1 | Fixed Type 30/30 ABS |
| Axle 2 | Fixed Type 30/30 NON ABS |
| Spring Ride Suspension | |
| 2-Speed Landing Gear | |
| Gooseneck | |
| King Pin Style | Fixed |
| King Pin Setting | 22" |
| Swing Clearance | 84" |
| 5th Wheel Height | 48" |
| King Pin | 2" Heavy Duty |
| Finish | |
| Sandblast & Powder Coat | |
| Mud Flaps & Reflective Tape | |
| Flag Holders | |

Dealer: