



FLAT BED, 25 TON
25FB381640



PRD: 00381640 A.1



FLAT BED, 25 TON
2 AXLE, MAXIMUM PAYLOAD 50,000 LBS



HIGH QUALITY STEEL

NuStrength™
HIGH PERFORMANCE STEEL

NuStrength™ HR100

**HIGH
PERFORMANCE
STEEL**

ULTRA HIGH STRENGTH SHEET
100 KSI / 700 MPA SHEET STEEL COMPARISON

Melted and Manufactured in the USA

Constructed with T-1 100K PSI yield strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

LANDING GEAR



2 speed Landing Gear, allows for 160,000 lbs static load.

DECKING OPTIONS



Oak: Standard.

Apitong: Best strength to weight ratios of natural woods.

Rubber: Composite which is impervious to fluids, mud, oil and UV rays.

REAR BUMPER



DOT certified rear under ride bumper with high visibility reflective tape and rubber docking bumpers.

WIDE TURN SIGNALS



Optional wide turn indicators available.

SUSPENSION



Tandem Air Ride Suspension.

WHEEL OPTIONS



All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.

COLOR CODED HOSES



Color coded air hoses allow for easy trouble shooting and maintenance.

WEB WINCHES




Web winches can be located on either side. Used to secure loads and objects on the trailer.

COLOR OPTIONS



Globe Trailers can powder coat to the color of your choice.

MOUNTED SPARE TIRE



Optional spare tire that mounts securely below the deck.

STEMCO WHEEL WARRANTY



5 year wheel end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

LIFTING LUGS



Air Transportable lifting Lugs.

LIGHTING SYSTEM



All Lighting is LED and mounted in rubber grommets to DOT standards.

RUB RAIL



2 1/2" rolled formed steel. 6" Structural Channel @ 6.5 lbs/ft, 5/16" Thick Stake Pockets 1 5/8" x 3 1/2" x 1/4", 24" O/C, 1/4" x 3" Rub rail.


POLYURETHANE VS RUBBER BUSHING



Reduced Maintenance	Increased Maintenance
Increased Trailer Lifetime	Needs Replacement
Increased Trailer Performance	Reduces Trailer Performance
Weather Resistant	Damaged from Weather



All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.



Trailer Model: GTFF252-40

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance	Swing Clearance
45'	8' 6"	49" (Loaded)	60" (Nominal)	60" (Nominal)	16"	122"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44" Standard
Side Rails	6" Channel
Crossmembers	4" I-Beam
Spacing	12"
Stake Pockets	24" center, both sides, front & rear, with rubrails.
Decking/Flooring	
Main Decking	1 3/8" Apitong
Electrical	
Lights	LED Plus 2 - Rear Strokes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	11R x 22.5 "H"
Rims	8.25 x 22.5 10 Hole Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Wide Turn Indicators	
Head Rack	
Web Winches	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30
Tandom Air Ride Sliding Suspension	
2-Speed Landing Gear.	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	36"
Swing Clearance	122"
5th Wheel Height	49"
King Pin	2" Heavy Duty

Dealer: