




DROP DECK, 40 TON
40DP313758



PRD-00313758 A.1



DROP DECK, 40 TON
2 AXLE, MAXIMUM PAYLOAD 80,000 LBS



HIGH QUALITY STEEL

NuStrength™
HIGH PERFORMANCE STEEL
NuStrength™ HR100

**HIGH
PERFORMANCE
STEEL**

ULTRA HIGH STRENGTH SHEET
100 KSI / 700 MPA SHEET STEEL COMPARISON

Melted and Manufactured in the USA

Constructed with T-1 100K PSI yield strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

STEMCO WHEEL WARRANTY



5 year wheel end warranty.
Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

LIGHTING SYSTEM



All Lighting is LED and mounted in rubber grommets to DOT standards.

COLOR OPTIONS



Globe Trailers can powder coat to the color of your choice

BEAVER TAIL



The Beavertail is an angled extension on the rear frame. This makes rear loading more convenient.

REAR SPRING RAMPS



Rear Spring Ramps upgrade available for easier use.

TRANSITION RAMPS



Pull out aluminum ramps built into neck to load wheeled vehicles onto upper deck.

RUB RAIL



2 1/2" rolled formed steel. 6" Structural Channel @ 6.5 lbs/ft, 5/16" Thick Stake Pockets 1 5/8" x 3 1/2" x 1/4", 24" O/C, 1/4" x 3" Rub rail.

HEAD RACK



Optional detachable steel bulkhead, 48" high with optional work lights.

WHEEL OPTIONS



All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.

LOCKABLE TOOL BOX



Optional Lockable Tool Box Mounted Underside of Main Deck, 24" x 24" x 48" Steel, can be located on either side.

DECKING OPTIONS



Oak: Standard.
Apitong: Best strength to weight ratios of natural woods.
Rumber: Composite which is impervious to fluids, mud, oil and UV rays.

COLOR CODED HOSES



Color coded air hoses allow for easy trouble shooting and maintenance.

WEB WINCHES



Web winches are welded on, located on the road side. Used to retain loads and objects on the trailer.

AIR BAGS



30K pound rated large diameter air bags are standard. This allows for lower operating pressure and higher capacity when needed.

LANDING GEAR



2 speed Landing Gear, allows for 160,000 lbs static load.


POLYURETHANE VS RUBBER BUSHING



Reduced Maintenance	Increased Maintenance
Increased Trailer Lifetime	Needs Replacement
Increased Trailer Performance	Reduces Trailer Performance
Weather Resistant	Damaged from Weather



All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.



Trailer Model: GTFS402-53-37

Weight: _____ ± lbs

Overall Length	Overall Width	Gooseneck Length	Lower Deck Height	Load Well Length	Beaver Tail Length	Ground Clearance
53'	8' 6"	10' 10"	43"	37'	5'	12"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	41" Standard
Side Rails	Structural Steel Channel
Crossmembers	4" on 12" Centers
Neck	Full Width
Outriggers	11 Per Side
Tie Downs	Sliding winches, Rub rail, Stake pockets and Straps.
Decking/Flooring	
Main Decking	2" Apitong
Electrical	
Lights	LED Plus 2 - Rear Strobes
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hole Hub Piloted Aluminum
Beavertail & Ramps	
Beavertail 5'	
Rear Ramps 24" x 60"	
Spring	
Steel Cleated	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	54"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30
Axle 2	Fixed Type 30/30 ABS
Air ride suspension, Manual dump valve.	
17" Travel, 2-Speed landing gear.	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	16"
Swing Clearance	91"
5th Wheel Height	46"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Dealer: