



DROP DECK, 40 TON
40DP510135



PRD: 00510135 A.1



DROP DECK, 40 TON
3 AXLE, MAXIMUM PAYLOAD 80,000 LBS



HIGH QUALITY STEEL

NuStrength™
HIGH PERFORMANCE STEEL
NuStrength™ HR100

**HIGH
PERFORMANCE
STEEL**

ULTRA HIGH STRENGTH SHEET
100 KSI / 700 MPA SHEET STEEL COMPARISON

Melted and Manufactured in the USA

Constructed with T-1 100K PSI yield strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

STEMCO WHEEL WARRANTY




5 year wheel end warranty.
Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

COLOR OPTIONS




Globe Trailers can powder coat to the color of your choice

WINCHES



Sliding Winch Track with 10 winches & straps

TOOL BOX




2 - Tool Boxes one each side, mounted under deck

WHEEL OPTIONS




All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.

MANUAL RAMPS



Manual Ramps placed at the rear of the Trailer for easy load ing & unloading



LIGHTING SYSTEM



All Lighting is LED and mounted in rubber grommets to DOT standards.

LANDING GEAR



2 speed Landing Gear, allows for 160,000 lbs static load.

COLOR CODED HOSES



Color coded air hoses allow for easy trouble shooting and maintenance.


POLYURETHANE VS RUBBER BUSHING



Reduced Maintenance	Increased Maintenance
Increased Trailer Lifetime	Needs Replacement
Increased Trailer Performance	Reduces Trailer Performance
Weather Resistant	Damaged from Weather



All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.




DECKING OPTIONS



Oak: Standard.

Apitong: Best strength to weight ratios of natural woods.

Rumber: Composite which is impervious to fluids, mud, oil and UV rays.



Trailer Model: GTFV403-53-37

Weight: _____ lbs

Overall Length	Overall Width	Gooseneck Length	Deck Length	Deck Height	Ground Clearance
53'	8' 6"	16'	37' 4"	38"	11 3/4"

Main Deck	
Main Beam	16" Fabricated I-Beam
Centers	40"
Side Rails	12" Channel
Crossmembers	10" & 4"
Spacing	12"
D-Rings	9 Each Side
Sliding Winch Track with 10 winches & straps	
Concentrated Load	80,000 lbs in 12'
Decking/Flooring	
Main Decking	2" Apitong
Wheel Covers	Steel Covered S-Plate
2 - Tool Boxes one each side, mounted under deck	
Electrical	
Lights	LED Plus -2 Rear Strobe
Connector	7 Way SAE Connector
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Rear Deck Options	
Removable Aluminum Rear Ramps 108" x 20" Stored on side of trailer	

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	49"
Axle Capacity	25,000 lbs
Brakes	16 1/2" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Super lift Type 30 Non-ABS
Air Ride Suspension	
2-Speed Landing Gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	18"
Swing Clearance	86"
5th Wheel Height	48"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

Dealer: