







TAG-A-LONG, 25 TON 3 AXLE, MAXIMUM PAYLOAD 50,000 LBS



TAG-A-LONG, 25 TON

FEATURES & BENEFITS





strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

WHEEL OPTIONS



All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.



D-rings on each side of the deck make it easier to secure loads to the trailer.

Hydraulic Ramps

Hydraulic ramp upgrade available for easier use.



The Beavertail is an angled extension on the rear frame. This makes rear loading more convenient.



25,000 lbs capacity axles.



2 speed Landing Gear, allows for 160,000 lbs static load.

COLOR OPTIONS



Globe Trailers can powder coat to the color of your choice.

LIGHTING SYSTEM



All Lighting is LED and mounted in rubber grommets to DOT standards.

STEMCO WHEEL WARRANTY



5 year wheel end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

SUSPENSION



Heavy duty tandem-axle spring ride suspension.

TAG-A-LONG, 25 TON

FEATURES & BENEFITS



DECKING OPTIONS



Oak: Standard. Apitong: Best strength to weight ratios of natural woods. Rumber: Composite which is impervious to fluids, mud, oil and UV rays.



Lockable tool box with anti theft provisions available.

HEAVY DUTY PINTLE EYE



3" Pintle eye, with 4 adjustable height positions, with 2 heavy duty safety chains and grab hooks.

WARRANTY



Globe Trailer's 5 year structural warranty on all lowboys is the best in the industry. Most competitors offer only a 5 year warranty. This shows how committed Globe Trailers is to it's customers.

COLOR CODED HOSES



Color coded air hoses allow for easy trouble shooting and maintenance.



Power pack option for rear hydraulic ramps.

POLYURETHANE VS RUBBER BUSHING





All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.





TAG-A-LONG, 25 TON 25TA850813



Trailer Model: GTTU253-34-24

Weight: Apx. : _____ ± lbs

Overall Length	Overall Width	Deck Length	D	eck Height	Beavertail Length		Drawbar Length
34' 2"	8' 6"	24' TA		34"		60"	62 ½"
Frame				Axles, Suspension, & Running Gear			
Main Beam	14 x 6.75 @ 30#	14 x 6.75 @ 30#			# of Axles 3		
Main Beam Centers	39″			Axle Spacir	ng	49"	
Side Rails	8" Channel			Axle Capac	ity	25,000 lbs	
Crossmembers	4" Jr. I Beams			Brakes		12 ¼" x 7 ½" - 25K	
Spacing	12"			ABS		2S1M	
Bumper	10" Channel			Axle 1		Super Lift Type 30 Non-ABS	
Header	8" Channel	8" Channel				Fixed Type 30/30 ABS	
# of D-Rings	11 Ea Side			Axle 3		Fixed Type 30/30 Non-ABS	
Drawbar				Suspension		Spring Ride 25K	
Tool Box Lockable w/ Steel Grating				Landing Gear		Dual 2-Speed 50K Drop Leg Jacks - 17"	
Hitch Type	3" Pintle Hitch	Grating		Tires & Rims			
Safety Chains with Hooks				Tires		235/75R x 17.5 "H"	
				Rims 6.75 X 17.5 Hub Piloted Steel			
Beavertail & Ramps				Hydraulics			
Beavertail 60"				Self Contained			
Rear Ramps 36" x 72"				Electric/Hydraulic w/Charge Kit			
Hydraulic, Cleated				Finish			
Electrical				Sandblast and Powder Coat			
Lights	LED Plus 2 - Rear Strobes			Mud Flaps & Reflective Tape			
2-Pole Plug to Power Hyd Ramps				Flag Holders			
Decking/Flooring				Dealer:			
Main Decking	1.75", Oak Full W	idth					
Beavertail Flooring	Steel Covered S-P	late w/Grousers					