DLA Contract
SPE8EC-19-D-0039

GSA Contract
GS-30F-0027R

GLOBE TRAILERS

TAG-A-LONG, 30 TON

30TA881324

PRD: 00881324 A.1

TAG-A-LONG, 30 TON

3 AXLE, MAXIMUM PAYLOAD 60,000 LBS

Powdercoated by GLOBE TRAILERS

Tag-A-Long, 30 Ton

Features & Benefits

High Quality Steel

Constructed with T-1 100K PSI yield strength steel. The high-tensile steel ensures the designed camber is retained and allows for a longer product service life.

Ramps

Adjustable with spring assist and safety bar.

Color Options

Globe Trailers can powder coat to the color of your choice.

Lighting System

All lighting is LED and mounted in rubber grommets to DOT standards.

Wheel Options

All Globe trailers come with standard hub-piloted disc wheels. All-aluminum wheels and aluminum outer wheels are also available.

Beaver Tail

The Beavertail is an angled extension on the rear frame. This makes rear loading more convenient.

STEMCO Wheel Warranty

5-year wheel-end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

Tie Downs

D-rings on each side of the deck make it easier to secure loads to the trailer.

Landing Gear

2 speed Landing Gear, allows for 160,000 lbs static load.

Suspension

Heavy duty tandem-axle spring ride suspension.

FEATURES & BENEFITS

DECKING OPTIONS

Oak: Standard. Apitong: Best strength-to-weight ratios among natural woods. Rumber: A composite impervious to fluids, mud, oil and UV rays.

HEAVY DUTY PINTLE EYE

3" Pintle eye, with 4 adjustable height positions, with 2 heavy duty safety chains and grab hooks.

COLOR CODED HOSES

Color-coded air hoses allow for easy troubleshooting and maintenance.

TOOL BOX

Lockable tool box with anti theft provisions available.

WARRANTY

WARRANTY 5 EXCLUSIVE 5 YEAR WARRANTY FIVE YEARS GLOBE TRAILERS

Globe Trailers' 5-year structural warranty on all lowboys is the best in the industry. Most competitors offer only a 5-year warranty. This shows how committed Globe Trailers is to its customers.

LIFT AXLE

The lift axle distributes the load across the other axles and reduces tire and axle wear. Keep it raised when unloaded and lowered when loaded.

POLYURETHANE VS RUBBER BUSHING

Reduced Maintenance	Increased Maintenance
Increased Trailer Lifetime	Needs Replacement
Increased Trailer Performance	Reduces Trailer Performance
Weather Resistant	Damaged from Weather

Powdercoated by GLOBE TRAILERS

All Globe Trailers are 100% powder-coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas-fired oven to optimum bonding temperature and applying an electrostatically charged zinc-rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a topcoat chosen from one of Globe Trailers' 188 color options is applied before the trailer returns to the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.

TAG-A-LONG, 30 TON

30TA881324



Trailer Model: GTBN303-35-24

Weight: Apx. : _____ ± lbs

Overall Length	Overall Width	Deck Length	Deck Height	Beavertail Length	Drawbar Length
34’ 2”	8’ 6”	24’ TA	34”	60”	62”

Frame	
Main Beam	14 x 6.75 @ 30#
Main Beam Centers	41”
Side Rails	8” Channel
Crossmembers	4” Jr. I Beams
Spacing	12”
Bumper	10” Channel
Header	8” Channel
# of D-Rings	10 Ea Side
Drawbar	
Tool Box	Lockable w/ Steel Grating
Hitch Type	3” Pintle Hitch
Safety Chains with Hooks	
Beavertail & Ramps	
Beavertail 60”	
Rear Ramps 36” x 72”	
Air Powered, Apitong Tread	
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7-way Connector
Decking/Flooring	
Main Decking	1 ⅜”, Apitong Full Width
Beavertail Flooring	Steel Covered S-Plate w/Grousers

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	49”
Axle Capacity	25,000 lbs
Brakes	12 ¼” x 7 ½” - 25K
ABS	2S1M
Axle 1	Super Lift Type 30 Non-ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30/30 Non-ABS
Suspension	Spring Ride 25K
Landing Gear	Hydraulic Dual 25k Landing Gear
Tires & Rims	
Tires	235/75R x 17.5 “H”
Rims	6.75 X 17.5 Hub Piloted Outer Aluminum
Hydraulics	
Self Contained	
Electric/Hydraulic w/Charge Kit	
Finish	
Sandblast and Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Dealer:

Globe Trailers | 3101 59th Ave Drive East, Bradenton, Florida 34203

1-800-800-3484 | www.globetrailers.com | sales@globetrailers.com